32-bit PCI BUS 10/100Mbps Fast Ethernet Adapter

User's Guide

1. Introduction

Thank you for purchasing our 10/100 Fast Ethernet Adapter, Fast Ethernet Adapter that provides the best possible performance. The RJ-45 port contains auto-negotiation functions that allow it to intelligently mediate between full and half-duplex modes. thereby facilitating the speed of migration between 10Base-T and 100Base-TX. Furthermore, when used with a switching hub that supports full duplex, the speed is effectively doubled to 20/200Mb. Lastly, on board LEDs and the diagnostic software provided make it a simple task to monitor an entire network's activity.

Designed in the plug-and-play solution, this Fast Ethernet Adapter's installation is hassle free, automatically configuring itself upon power-up to avoid conflicts. Its comprehensive and intelligent auto-install software installs the correct driver for the network operating system of your choices.

2. Features & Technical Specification

(1) Features

- Complies with the IEEE802.3 CSMA/CD, 100Base-TX and 10Base-T standard.
- Support 32-bit PCI Bus Master for high performance and low processor utilization.
- Full duplex design to double the performance to 20Mbps/200Mbps.
- Support Auto-negotiation function.
- Auto-setups IRQ and I/O address.
- Built-in FIFO buffers to eliminate external memory.
- One STP connector for 100Mbps or 10Mbps network speed.
- Supports early interrupt on transmit to increase performance.
- Supports ODI driver for NetWare 3.x/4.x; NDIS driver for LAN Manager, Windows 95, Windows 98, Windows NT: Packet Driver for TCP/IP software.
 - Provides diagnostic software and LEDs to indicate network status.
- Supports smart remote Boot ROM (optional)
- Supports APCI Wake on LAN (optional)

(2) Technical Specification

Topology : Star Connector : RJ-45

Standard : IEEE802.3 10Base-T: IEEE802.3 100Base-TX Transmission Rate : 10Mbps or 20Mbps; 100Mbps or 200Mbps

: IBM compatible PC with available PCI slot Hardware Required

RQ Line : Assgned by system I/O Address : Assigned by system

Drivers : ODI driver for NetWare 3.x/4.x NDIS driver for LAN Manager.

Windows 95, Windows 98, Windows NT, Packet Driver for TCP/IP software

: 0°C to 55°C (Operating) Temperature Humidity : 10% to 90% (Non-condensing)

Certification : FCC Class B. CE Mark : 1.8W (Max.)

Power consumption

3. Installation

(1) Hardware Installation

To insert the network adapter into your PC, follow the steps bellow:

- 1. Turn off the computer and remove its cover.
- 2. Insert the adapter into a PCI slot.
- 3. Secure this adapter to the rear of the computer chassis and put back the computer cover.
- 4. Connect the adapter to the network using twisted-pair cable.

(2) Driver Installation

Use the drivers supplied by the diskette included in this product. For detail description, please refer to the diskette provides by this product.

4. Trouble-shooting

If you experience any problems with the adapter, first make sure the appropriate driver is loaded, the proper cable is connected to the adapter port and the hub complies with the adapter specification, such as 10Mbps 10Base-T or 100Mbps 10Base-TX, then check the LED.

The adapter provides easy LEDs to indicate network status.

FCC COMPLIANCE STATEMENT

This equipment has been tested and found to comply with the limits of a Class B computing devices, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. If you suspect this product is causing interference, turn your computer on and off while your radio or TV is showing interference. If the interference disappears then when you turn the computer off and reappears then you turn the computer on, something in the computer is causing interference. You can try to correct the interference by one or more of the following measures:

- 1. Reorient/Relocate the receiving antenna.
- 2. Increase the separation between the equipment and receiver.
- $3. \, \text{Connect the equipment into an outlet on a circuit difference from that to which the receiver is connected.} \\$
- 4. Ensure that all expansion slots (on the back or side of the computer) are covered. Also ensure that all metal retaining brackets are tightly attached to the computer.

All brand and product names are the trademarks and/or registered trademarks of their respective companies.

GigaFast Ethernet Technical Support Department Hours of Operation Monday - Friday 9am - 5:30pm (Pacific Time) Excluding Holidays 1(888) GFE-6788 / 1(888) 433-6788

GigaFast's Limited Warranty

Limited Warranty Statement: GigaFast Ethernet Solutions Inc. ("GFE") warrants its products to be free from defects in workmanship and materials, under normal use and service, for the applicable warranty term. All GFE products carry a standard limited warranty from the date of purchase from GFE or its Authorized Reseller. GFE may, at its own discretion, repair or replace any product not operating as warranted with a similar or functionally equivalent product, during the applicable warranty term.

All products that are replaced become the property of GFE. Replacement products may be either new or reconditioned. Any replaced or repaired product carries either a 30-day limited warranty or the remainder of the initial warranty, whichever is longer. GFE is not responsible for any custom software or firmware, configuration information, or memory data of Customer contained in, stored on, or integrated with any products returned to GFE pursuant to any warranty. Products returned to GFE should have any customer-installed accessory or add-on components, such as expansion modules, removed prior to returning the product for replacement. GFE is not responsible for these items if they are returned with the product.

Customers must contact GFE for a Return Material Authorization number prior to returning any product to GFE. Proof of purchase may be required. Any product returned to GFE without a valid Return Material Authorization (RMA) number clearly marked on the outside of the package will be returned to customer at customer's expense. For warranty claims within North America, please call our foll-free customer support number at (888) GFE-6788/(888) 433-6788. Customers are responsible for all shipping charges from the facility to GFE. GFE is responsible for return shipping charges from GFC outsomer.

WARRANTIES EXCLUSIVE: IF A GFE PRODUCT DOES NOT OPERATE AS WARRANTED ABOVE, CUSTOMER'S SOLE REMEDY SHALL BE REPAIR OR REPLACEMENT OF THE PRODUCT IN QUESTION, AT GFE'S OPTION. THE FOREGOING WARRANTIES AND REMEDIES ARE EXCLUSIVE AND ARE IN LIEU OF ALL OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, EITHER IN FACT OR BY OPERATION OF LAW, STATUTORY OR OTHERWISE, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, GFE NEITHER ASSUMES NOR AUTHORIZES ANY OTHER PERSON TO ASSUME FOR IT ANY OTHER LIABILITY IN CONNECTION WITH THE SALE, INSTALLATION, MAINTEMANCE OR USE OF ITS PRODUCTS, GFE SHALL NOT BE LIABLE UNDER THIS WARRANTY IF ITS TESTING AND EXAMINATION DISCLOSE THE ALLEGED DEFECT IN THE PRODUCT DOES NOT EXIST OR WAS CAUSED BY CUSTOMER'S OR ANY THIRD PERSONS MISUSE, NEGLECT, IMPROPER INSTALLATION OR TESTING, UNAUTHORIZED ATTEMPTS TO REPAIR, OR ANY OTHER CAUSE BEYOND THE RANGE OF THE INTENDED USE. OR BY ACCIDENT. FIRE LIGHTNING, OR OTHER HAZAGO

LIMITATION OF LIABILITY: IN NO EVENT, WHETHER BASED IN CONTRACT OR TORT (INCLUDING NEGLIGENCE), SHALL GFE BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL, INDIRECT, SPECIAL, OR PUNITIVE DAMAGES OF ANY KIND, OR FOR LOSS OF REVENUE, LOSS OF BUSINESS, OR OTHER FINANCIAL LOSS ARISING OUT OF OR IN CONNECTION WITH THE SALE, INSTALLATION, MAINTENANCE, USE, PERFORMANCE, FAILURE, OR INTERRUPTION OF ITS PRODUCTS, EVEN IF GFE OR ITS AUTHORIZED RESELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

SOME STATES DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES OR THE LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR CONSUMER PRODUCTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, WHICH MAY VARY FROM STATE TO STATE. NOTHING IN THIS WARRANTY SHALL BE TAKEN TO AFFECT YOUR STATILTORY RIGHTS.

*GFE will provide warranty service for one year following discontinuance from the active GFE price list. Under the limited lifetime warranty, internal and external power supplies, fans, and cables are covered by a standard one-year warranty from date of purchase.